

LVT gluedown only

Specification



plank



herringbone



tile

Planks per Pack	10	28	18
Pack Coverage	2.27m ²	1.48m ²	3.24m ²
Packs per Pallet	100	140	66
Pallet Coverage	227m ²	207.20m ²	213.84m ²
Plank Dimensions	1229 x 185 mm	460 x 115 mm	600 x 300 mm
Wear Layer	0.70 mm	0.70 mm	0.70 mm
Thickness	3.0 mm	3.0 mm	3.0 mm
Total Weight	13.4 kg	8.8 kg	19 kg

Performance

Castor Chair Wheel (EN ISO 4918)	Pass
Abrasion Resistance (EN ISO 660-2)	T Grade
Colour Fastness (EN ISO 105-B02)	≥6
Fire Rating (BS EN 13501-1)	B _{FL} -s1
Effects of Stain (BS EN 423)	Pass
Residual Indentation (BS EN 24343-1)	≤ 0.10mm
Dimensional Stability (EN ISO 23999)	X ≤ 0.15% Y ≤ 0.15%
Curling Resultant to Heat (EN ISO 23999)	≤ 1.0mm
Chemical Resistance (EN ISO 26987)	Index 0
Slip Resistance (BS EN 7976)	36+ (wet & dry conditions)
Slip Resistance (BS EN 16165 Annex B)	R10 (Plank + Herringbone) R9 (Tile)
Performance Classification (EN ISO 10874)	23/33/42
Impact Sound Reduction (EN ISO 10140-3)	3 dB
Phthalate Content (EN ISO 14389)	≤ 0.01% (Pass)
VOC Emissions (BS EN 16516)	ND (Pass)