

LVT gluedown

Specification



plank



herringbone

Planks per Pack	12	32
Pack Coverage	2.73m ²	2.23m ²
Packs per Pallet	100	112
Pallet Coverage	273m ²	249.76m ²
Plank Dimensions	1220 x 185 mm	590 x 118 mm
Wear Layer	0.55 mm	0.55 mm
Thickness	2.5 mm	2.5 mm
Total Weight per Pack	12.5 kg	10.5 kg

Performance

Castor Chair Wheel (EN ISO 4918)	Pass
Abrasion Resistance (EN ISO 660-2)	T Grade
Colour Fastness (EN ISO 105-B02)	≥6
Fire Rating (BS EN 13501-1)	B _{FL} -s1
Effects of Stain (BS EN 423)	Pass
Residual Indentation (BS EN 24343-1)	≤ 0.10mm
Dimensional Stability (EN ISO 23999)	X ≤ 0.15% Y ≤ 0.15%
Curling Resultant to Heat (EN ISO 23999)	≤ 1.0mm
Chemical Resistance (EN ISO 26987)	Index 0
Slip Resistance (BS EN 7976)	36+ (dry conditions)
Slip Resistance (BS EN 16165 Annex B)	R10
Performance Classification (EN ISO 10874)	23/33/42
Impact Sound Reduction (EN ISO 10140-3)	3 dB
Phthalate Content (EN ISO 14389)	≤ 0.01% (Pass)
VOC Emissions (BS EN 16516)	ND (Pass)