

LVT gluedown

Specification



plank



herringbone

Planks per Pack	10	16
Pack Coverage	2.23m ²	1.114m ²
Packs per Pallet	70	112
Pallet Coverage	156.10m ²	124.77m ²
Plank Dimensions	1220 x 183 mm	590 x 118 mm
Wear Layer	0.55 mm	0.55 mm
Thickness	4.0 mm + 1.0 mm underlay	5.0 mm + 1.0 mm underlay
Total Weight per Pack	18 kg	18 kg

Performance

Castor Chair Wheel (EN ISO 4918)	Pass
Abrasion Resistance (EN ISO 660-2)	T Grade
Colour Fastness (EN ISO 105-BO2)	≥6
Fire Rating (BS EN 13501-1)	B _{FL} -s1
Effects of Stain (BS EN 423)	Pass
Residual Indentation (BS EN 24343-1)	≤ 0.10mm
Dimensional Stability (EN ISO 23999)	X ≤ 0.15% Y ≤ 0.15%
Curling Resultant to Heat (EN ISO 23999)	≤ 1.0mm
Chemical Resistance (EN ISO 26987)	Index 0
Slip Resistance (BS EN 7976)	36+ (dry conditions)
Slip Resistance (BS EN 16165 Annex B)	R10
Performance Classification (EN ISO 10874)	23/33/42
Impact Sound Reduction (EN ISO 10140-3)	3 dB
Phthalate Content (EN ISO 14389)	≤ 0.01% (Pass)
VOC Emissions (BS EN 16516)	ND (Pass)